

# S30SC4M

40V 30A

## FEATURES

- $T_j=150^\circ\text{C}$
- $P_{RRSM}$  avalanche guaranteed
- Small  $\theta_{jc}$
- High current capacity


## APPLICATION

- Switching power supply
- DC/DC converter
- Home Appliances, Office Equipment
- Telecommunication

## OUTLINE DIMENSIONS

Case : MTO-3P

Unit : mm



## RATINGS

### ● Absolute Maximum Ratings (If not specified $T_c=25^\circ\text{C}$ )


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	$T_{stg}$		-40~150	$^\circ\text{C}$
Operating Junction Temperature	$T_j$		150	$^\circ\text{C}$
Maximum Reverse Voltage	$V_{RM}$		40	V
Repetitive Peak Surge Reverse Voltage	$V_{RRSM}$	Pulse width 0.5ms, duty 1/40	45	V
Average Rectified Forward Current	$I_o$	50Hz sine wave, R-load, Rating for each diode $I_o/2$ , $T_c=126^\circ\text{C}$	30	A
Peak Surge Forward Current	$I_{FSM}$	50Hz sine wave, Non-repetitive 1 cycle peak value, $T_j=125^\circ\text{C}$	300	A
Repetitive Peak Surge Reverse Power	$P_{RRSM}$	Pulse width 10 $\mu\text{s}$ , Rating of per diode, $T_j=25^\circ\text{C}$	1000	W
Mounting Torque	$T_{OR}$	(Recommended torque: 0.5N·m)	0.8	N·m

### ● Electrical Characteristics (If not specified $T_c=25^\circ\text{C}$ )

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	$V_F$	$I_F=15\text{A}$ , Pulse measurement, Rating of per diode	Max.0.55	V
Reverse Current	$I_R$	$V_R=V_{RM}$ , Pulse measurement, Rating of per diode	Max.10	mA
Junction Capacitance	$C_j$	$f=1\text{MHz}$ , $V_R=10\text{V}$ , Rating of per diode	Typ.590	pF
Thermal Resistance	$\theta_{jc}$	junction to case	Max.1.0	$^\circ\text{C}/\text{W}$

S30SC4M

Junction Capacitance



Reverse Voltage  $V_R$  [V]

0.05 0.2 0.5 2 5 20 50 200 500 2000 5000

0.002 0.005 0.02 0.05 0.2 0.5 2 5 20

*Made in China*